


Product and Submittal Data

Single Packaged Cooling/Electric Heat Entry, Convertible, 2 to 5 Ton, R-454B

A5PA3024A1000A
A5PA3030A1000A
A5PA3036A1000A
A5PA3042A1000A
A5PA3048A1000A
A5PA3060A1000A



Note: Graphics in this document are for representation only. Actual model may differ in appearance.

Introduction

Single Packaged Cooling Systems are easy and versatile to install.

Because cooling and air handling functions are all contained in a single cabinet, Trane packaged air conditioners are easy to install and service. It can be flush mounted beside your home at ground level or placed on the roof for horizontal or downflow installation. When connected to an optional Trane thermostat control, and air distribution ducts, you have a highly efficient, total home comfort system.

Single Packaged Cooling Systems are unmatched in quality and reliability.

All major components on these products, including the compressor, have been designed and manufactured for maximum service. Every compressor is designed and manufactured to exacting specifications. Each design is life tested in extreme environments to ensure reliable and long lasting operation in normal applications. Each compressor has internal motor protection for added reliability.

Copyright

This document and the information in it are the property of Trane, and may not be used or reproduced in whole or in part without written permission. Trane reserves the right to revise this publication at any time, and to make changes to its content without obligation to notify any person of such revision or change.

Trademark

All trademarks referenced in this document are the trademarks of their respective owners.

Data Notes

This document supersedes and includes data from the documents listed below.

Table 1. Data notes

Literature Number	Title
A5PA3024A-SUB-1*	Single Packaged Cooling/Electric Heat Model A5PA3024A1000A Submittal
A5PA3030A-SUB-1*	Single Packaged Cooling/Electric Heat Model A5PA3030A1000A Submittal
A5PA3036A-SUB-1*	Single Packaged Cooling/Electric Heat Model A5PA3036A1000A Submittal
A5PA3042A-SUB-1*	Single Packaged Cooling/Electric Heat Model A5PA3042A1000A Submittal
A5PA3048A-SUB-1*	Single Packaged Cooling/Electric Heat Model A5PA3048A1000A Submittal
A5PA3060A-SUB-1*	Single Packaged Cooling/Electric Heat Model A5PA3060A1000A Submittal

Table of Contents

- Optional Equipment Listing 4
- Product Specification 5
- Supplementary Electric Heaters 7
- BAYSPEK - Single Power Entry Kit 9
- Indoor Fan Performance (230V) 10
- Wiring Diagrams..... 13
- Full Perimeter Roof Mounting Curb 19
- Optional Equipment — Outside Air Damper 21
- Optional Equipment — Filter Rack 22
- Dimensional Data..... 23
- Mechanical Specifications 25

Optional Equipment Listing

Table 2. Optional equipment listing

454 Model Number	Use With
Hinged Filter Access Door (A5PA3024-36)	BAYACCDOR1A []
Hinged Filter Access Door (A5PA3042-60)	BAYACCDOR2A []
Adapter Curb (Cabinet A/B) (A5PA3024-36)	BAYADAP050A []
Adapter Curb (Cabinet C) (A5PA3024-36)	BAYADAP051A []
Adapter Curb (Cabinet A/B) (A5PA3042-60)	BAYADAP052A []
Adapter Curb (Cabinet C) (A5PA3042-60)	BAYADAP053A []
Adapter Curb (Cabinet D) (A5PA3042-60)	BAYADAP054A []
Anti-Short Cycle Timer (A5PA3024-60)	BAYASCT001 []
Crankcase Heater (230V) (Scroll) (A5PA3042-60)	BAYCCHT102A []
Crankcase Heater (230V) (Scroll) (A5PA3024-36)	BAYCCHT103A []
Flat Roof Full Perimeter Curb (Insulated) (A5PA3024-36)	BAYCURB050A []
Flat Roof Full Perimeter Curb (Insulated) (A5PA3042-60)	BAYCURB051A []
Extreme Conditions Mounting Kit (Used on BAYCURB & BAYADAP) (A5PA3024-60)	BAYEXMK001A []
Extreme Conditions Mounting Kit (Used on BAYUTIL) (A5PA3024-60)	BAYEXMK002B []
Extreme Conditions Mounting Kit (Used on Slab Mounts) (A5PA3024-60)	BAYEXMK003A []
1-2" Filter Frame-Requires one 18x25 filter (not included) (A5PA3024-36)	BAYFLTR101C []
1-2" Filter Frame-Requires one 18x20, and one 18x18 filter (not included) (A5PA3042-60)	BAYFLTR201C []
Supplementary Electric Heater - 1ph 5kW (A5PA3024-60)	BAYHTRG105A []
Supplementary Electric Heater - 1ph 8kW (A5PA3024-60)	BAYHTRG108A []
Supplementary Electric Heater - 1ph 10kW (A5PA3024-60)	BAYHTRG110A []
Supplementary Electric Heater - 1ph 15kW (A5PA3030-60)	BAYHTRG115A []
Supplementary Electric Heater - 1ph 20kW (A5PA3048-60)	BAYHTRG120A []
Supplementary Electric Heater - 1ph 25kW (A5PA3060)	BAYHTRG125A []
Single Power Entry Kit (A5PA3024-42)	BAYSPEK60J []
Single Power Entry Kit (A5PA3024-60)	BAYSPEK62J []
Single Power Entry Kit (A5PA3030-60)	BAYSPEK63J []

Product Specification

Table 3. Product specification

MODEL	A5PA3024	A5PA3030	A5PA3036	A5PA3042	A5PA3048	A5PA3060
RATED Volts/PH/Hz	208–230/1/60					
Performance Cooling BTUH ^(a)	24000	28400	36800	40000	47500	58500
Indoor Airflow (CFM)	820	920	1190	1500	1670	1700
Power Input (KW)	LOCATED ON UNIT NAMEPLATE					
EER2/SEER2 (BTU/Watt-Hr.) ^(b)	10.6/13.4					
Sound Power Rating [dB(A)] ^(c)	66.6	70	69.3	74.6	72.5	73.1
POWER CONN. — V/Ph/Hz	208–230/1/60					
Min. Brch. Cir. Ampacity ^(d)	LOCATED ON UNIT NAMEPLATE					
Fuse Size — Max. (amps)	25	30	40	40	50	60
Fuse Size — Recmd. (amps)	25	30	40	40	50	60
COMPRESSOR	SCROLL					
Volts/Ph/Hz	208–230/1/60					
R.L. Amps — L.R. Amps	LOCATED ON UNIT NAMEPLATE					
OUTDOOR COIL — TYPE	SPINE-FIN					
Rows/F.P.I	2 / 24					
Face Area (sq. ft.)	13.32	13.32	15.49	15.63	20.54	22.99
Tube Size (in.)	3/8					
INDOOR COIL — TYPE	MCHE					RTPF
Rows/F.P.I	2 / 16					4 / 15
Face Area (sq. ft.)	2.7			3.9	3.9	5.0
Tube Size (in.)	0.81	0.81	1.00	0.81	0.81	0.38
Refrigeration Control	EXPANSION VALVE					
Drain Conn. Size (in.)	3/4 FEMALE NPT					
OUTDOOR FAN — TYPE	PROPELLER					
DIA. (IN.)	23.4			28.3		
DRIVE/NO. SPEEDS	DIRECT / 1					
CFM @ 0.0 in. w.g ^(e)	2350	2800	3080	3400	3400	4800
Motor — HP/R.P.M	1/12 /825	1/6 /825	1/5 / 825	1/4 / 825	1/4 / 825	1/3 / 825
Volts/Ph/Hz	208–230/1/60					
F.L. Amps/L.R Amps	LOCATED ON UNIT NAMEPLATE					
INDOOR FAN — TYPE	CONSTANT TORQUE ECM					
Dia. x Width (in.)	10.62 X 10.62					11.87 X 10.62
Drive/No. Speeds	DIRECT / 4					
CFM @ 0.0 in. w.g ^(f)	SEE FAN PERFORMANCE TABLE					
Motor — HP / R.P.M.	1/3 / 1050	1/2 / 1050	3/4 / 1050			1 / 1050

Product Specification

Table 3. Product specification (continued)

MODEL	A5PA3024	A5PA3030	A5PA3036	A5PA3042	A5PA3048	A5PA3060
Volts/Ph/Hz	208-230/1/60					
F.L. Amps	LOCATED ON UNIT NAMEPLATE					
FILTER / FURNISHED	NO					
Type Recommended	THROWAWAY					
Recmd. Face Area (sq. ft) ⁽⁹⁾	4			5.3		
REFRIGERANT	R-454B					
Charge (lbs.)	LOCATED ON UNIT NAMEPLATE					
CHARGING SPECIFICATIONS						
Subcooling	12° F	10° F	12° F	12° F	10° F	13° F
DIMENSIONS	H X W X L					
Crated (in.)	46 X 45 X 52	48 X 45 X 52	48 X 45 X 52	46 X 47 X 62	50 X 47 X 61	50 X 47 X 61
WEIGHT						
Shipping (lbs.) / Net (lbs.)	436 / 362	454 / 380	458 / 384	564 / 460	564 / 460	589 / 485

^(a) Rated in accordance with AHRI Standard 210/240.

^(b) Rated in accordance with D.O.E. test procedure.

^(c) Sound Power values are not adjusted for AHRI 270-95 tonal corrections.

^(d) Calculated in accordance with currently prevailing Nat'l Electrical Code.

^(e) Standard Air — Dry Coil — Outdoor.

^(f) Standard Air — Dry Coil — Indoor

^(g) Filters must be installed in return air stream. Square footages listed are based on 300 f.p.m. face velocity. If permanent filters are used size per manufacturer's recommendation with a clean resistance of 0.05" W.C.

Supplementary Electric Heaters

Table 4. Supplementary electric heaters

UNIT MODEL	ELECTRIC HEATER MODEL	RATED VOLT-AGE	PHASE	AMPS	HEATER CAPACITY		NO. OF STAGES	KW/STAGE		MCA	MAX. FUSE OR HACR CKT BKR SIZE (a)	CANADA ONLY MAX. CKT BKR SIZE (b)
					KW	BTUH		1	2			
&TCC&024-060+1 &WCC&024-060+1 &TCY&024-060+1 &WCY&024-060+1 &WCZ&024-060+1 A5PA&024-060+1 A5PH&024-060+1	BAYHTRG105	208/240	1	18/21	3.76/5.0	12800/ 17100	1	3.76/ 5.0	-	23/26	25/30	25/30
&TCC&024-060+1 &WCC&024-060+1 &TCY&024-060+1 &WCY&024-060+1 &WCZ&024-060+1 A5PA&024-060+1 A5PH&024-060+1	BAYHTRG108	208/240	1	29/33	6.0/8.0	20500/ 27300	1	6.0/8.0	-	36/41	40/45	40/45
&TCC&024-060+1 &WCC&024-060+1 &TCY&024-060+1 &WCY&024-060+1 &WCZ&024-060+1 A5PA&024-060+1 A5PH&024-060+1	BAYHTRG110	208/240	1	36/42	7.5/10.0	25600/ 34100	1	7.5/ 10.0	-	45/52	45/60	45/60
&TCC&030-060+1 &WCC&030-060+1 &TCY&030-060+1 &WCY&030-060+1 &WCZ&036+1 &WCZ&048+1 &WCZ&060+1 A5PA&030-060+1 A5PH&030-060+1	BAYHTRG115	208/240	1	54/63	11.27/ 15.0	38500/ 51200	2	7.5/ 10.0	3.76/ 5.0	68/78	70/80	70/80
&TCC&048-060+1 &WCC&048-060+1 &TCY&042-060+1 &WCY&042-060+1 &WCZ&048-060+1 A5PA&048-060+1 A5PH&048-060+1	BAYHTRG120#	208/240	1	72/83	15.0/ 20.0	51200/ 68300	2	7.5/ 10.0	7.5/ 10.0	90/ 104	90/110	90/110
&TCC&060+1 &WCC&060+1 &TCY&042-060+1 &WCY&042-060+1 &WCZ&048-060+1 A5PA&060+1 A5PH&060+1	BAYHTRG125#	208/240	1	90/ 104	18.78/ 25.0	64100/ 85300	2	11.26/ 15.0	7.5/ 10.0	113/ 130	125/150	125/150
&W/TCY4036-060+3 &WCZ&036-060+3	BAYHTRV305	208/240	3	10/ 12	3.76/ 5.0	12800/ 17100	1	3.76/ 5.0	—	13/ 15	15/15	15/15
&W/TCY4036-060+3 &WCZ&036-060+3	BAYHTRV308	208/240	3	17/ 19	6.0/ 8.0	20500/ 27300	1	6.0/ 8.0	—	21/ 24	25/25	25/25
&W/TCY4036-060+3 &WCZ&036-060+3	BAYHTRV310	208/240	3	21/ 24	7.5/ 10.0	25600/ 34100	1	7.5/ 10.0	—	26/ 30	30/30	30/30
&W/TCY4036-060+3 &WCZ&036-060+3	BAYHTRV315	208/240	3	31/ 36	11.27/ 15.0	38500/ 51200	2	7.5/ 10.0	3.76/ 5.0	39/ 45	40/45	40/45
&W/TCY4048-060+3 &WCZ&048-060+3	BAYHTRV320	208/240	3	42/ 48	15.0/ 20.0	51200/ 68300	2	7.5/ 10.0	7.5/ 10.0	52/ 60	60/60	60/60
&W/TCY4048-060+3 &WCZ&048-060+3	BAYHTRV325#	208/240	3	52/ 60	18.78/ 25.0	64100/ 85300	2	11.26/ 15.0	7.5/ 10.0	65/ 75	70/80	70/80

Supplementary Electric Heaters

Table 4. Supplementary electric heaters (continued)

UNIT MODEL	ELECTRIC HEATER MODEL	RATED VOLT-AGE	PHASE	AMPS	HEATER CAPACITY		NO. OF STAGES	KW/STAGE		MCA	MAX. FUSE OR HACR CKT BKR SIZE ^(a)	CANADA ONLY MAX. CKT BKR SIZE ^(b)
					KW	BTUH		1	2			
&WCZ&036-060#4	BAYHTRV405	480	3	6	5.0	17100	1	5.0	—	8	15	15
&WCZ&036-060#4	BAYHTRV408	480	3	10	8.0	27300	1	8.0	—	13	15	15
&WCZ&036-060#4	BAYHTRV410	480	3	12	10.0	34100	1	10.0	—	15	15	15
&WCZ&036-060#4	BAYHTRV415	480	3	18	15.0	51200	2	10.0	5.0	23	25	25
&WCZ&048-060#4	BAYHTRV420	480	3	24	20.0	68300	2	10.0	10.0	30	30	30
&WCC&036-060#3	BAYHTRG305	208/240	3	10/12	3.76/5.0	12800/17100	1	3.76/5.0	-	13/15	15/15	15/15
&WCC&036-060#3	BAYHTRG308	208/240	3	17/19	6.0/8.0	20500/27300	1	6.0/8.0	-	21/24	25/25	25/25
&WCC&036-060#3	BAYHTRG310	208/240	3	21/24	7.5/10.0	25600/34100	1	7.5/10.0	-	26/30	30/30	30/30
&WCC&036-060#3	BAYHTRG315	208/240	3	31/36	11.27/15.0	38500/51200	2	7.5/10.0	3.76/5.0	39/45	40/45	40/45
&WCC&048-060#3	BAYHTRG320	208/240	3	42/48	15.0/20.0	51200/68300	2	7.5/10.0	7.5/10.0	52/60	60/60	60/60
&WCC&048-060#3	BAYHTRG325#	208/240	3	52/60	18.78/25.0	64100/85300	2	11.26/15.0	7.5/10.0	65/75	70/80	70/80
&WCC&036-060#4	BAYHTRG405	480	3	6	5.0	17100	1	5.0	-	8	15	15
&WCC&036-060#4	BAYHTRG408	480	3	10	8.0	27300	1	8.0	-	13	15	15
&WCC&036-060#4	BAYHTRG410	480	3	12	10.0	34100	1	10.0	-	15	15	15
&WCC&036-060#4	BAYHTRG415	480	3	18	15.0	51200	2	10.0	5.0	23	25	25
&WCC&048-060#4	BAYHTRG420	480	3	24	20.0	68300	2	10.0	10.0	30	30	30

1. Any power supply and circuits must be wired and protected in accordance with local electrical codes.
2. The values listed in the above table are for the electric heater only.
3. Field wiring must be rated at least 75° C.
4. * indicates an alpha character.
5. † indicates model letter.
6. # Heater uses fuses.
7. & indicates a digit.

ALL VALUES ARE FOR THE ELECTRIC HEATER ONLY

^(a) The HACR circuit breaker is for U.S.A. installations only.

^(b) For Canada installation reference only.

BAYSPEK - Single Power Entry Kit

Table 5. BAYSPEK — Single power entry kit

SINGLE CIRCUIT POWER AMPACITY AND OVER CURRENT PROTECTION				
UNIT MODEL	SINGLE POWER ENTRY KIT	HEATER MODEL	MIN CKT AMP	MAX OVER-CURRENT DEVICE
A5PA3024A	BAYSPEK60	BAYHTRG105	29	30
		BAYHTRG108	45	45
		BAYHTRG110	56	60
A5PA3030A	BAYSPEK60	BAYHTRG105	31	35
		BAYHTRG108	47	50
		BAYHTRG110	57	60
	BAYSPEK63	BAYHTRG115	83	90
A5PA3036A	BAYSPEK60	BAYHTRG105	34	40
		BAYHTRG108	49	50
		BAYHTRG110	60	60
	BAYSPEK63	BAYHTRG115	86	90
A5PA3042A	BAYSPEK60	BAYHTRG105	34	40
		BAYHTRG108	49	50
		BAYHTRG110	60	60
	BAYSPEK63	BAYHTRG115	86	90
A5PA3048A	BAYSPEK60	BAYHTRG105	36	50
		BAYHTRG108	49	50
		BAYHTRG110	60	60
	BAYSPEK63	BAYHTRG115	86	90
		BAYHTRG120	112	125
A5PA3060A	BAYSPEK60	BAYHTRG105	41	60
		BAYHTRG108	51	60
	BAYSPEK62	BAYHTRG110	61	70
	BAYSPEK63	BAYHTRG115	87	90
		BAYHTRG120	113	125

Indoor Fan Performance (230V)

Table 6. Indoor fan performance – model A5PA3024

A5PA3024		EXTERNAL STATIC PRESSURE (IN.WG) Horizontal Airflow [Cooling Down Airflow]										
Motor Speed		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
LOW	Watts	84 [85]	91 [92]	98 [98]	105 [106]	-	-	-	-	-	-	-
	CFM	873 [865]	811 [803]	754 [746]	690 [683]	-	-	-	-	-	-	-
MED-LOW ^(a)	Watts	-	114 [115]	121 [122]	128 [129]	138 [138]	-	-	-	-	-	-
	CFM	-	900 [891]	846 [838]	794 [786]	729 [722]	-	-	-	-	-	-
MED-HIGH	Watts	-	-	-	158 [159]	167 [167]	175 [176]	185 [186]	-	-	-	-
	CFM	-	-	-	890 [881]	836 [828]	777 [769]	707 [700]	-	-	-	-
HIGH	Watts	-	-	-	-	- [249]	256 [258]	264 [266]	274 [276]	282 [284]	-	-
	CFM	-	-	-	-	- [899]	863 [854]	818 [810]	773 [765]	731 [724]	-	-

Note: Airflow must not exceed 900 CFM due to condensate blowoff.

^(a) Factory Default Setting.

Table 7. Indoor fan performance – model A5PA3030

A5PA3030		EXTERNAL STATIC PRESSURE (IN.WG) Horizontal Airflow [Cooling Down Airflow]										
Motor Speed		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
LOW	Watts	126 [126]	134 [135]	142 [143]	150 [150]	158 [158]	-	-	-	-	-	-
	CFM	1051 [1041]	994 [984]	939 [930]	889 [880]	840 [831]	-	-	-	-	-	-
MED-LOW ^(a)	Watts	-	175 [176]	184 [185]	192 [193]	200 [201]	209 [210]	219 [220]	-	-	-	-
	CFM	-	1107 [1096]	1054 [1044]	1009 [999]	965 [956]	919 [910]	862 [853]	-	-	-	-
MED-HIGH	Watts	-	-	239 [240]	247 [248]	256 [258]	267 [269]	274 [276]	282 [284]	-	-	-
	CFM	-	-	1108 [1097]	1070 [1059]	1027 [1017]	975 [965]	920 [911]	875 [866]	-	-	-
HIGH	Watts	-	-	-	-	259 [260]	268 [270]	278 [279]	289 [290]	-	-	-
	CFM	-	-	-	-	1099 [1088]	1059 [1048]	1017 [1007]	968 [959]	-	-	-

Note: Airflow must not exceed 1125 CFM due to condensate blowoff.

^(a) Factory Default Setting.

Table 8. Indoor fan performance – model A5PA3036

A5PA3036		EXTERNAL STATIC PRESSURE (IN.WG) Horizontal Airflow [Cooling Down Airflow]										
Motor Speed		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
LOW	Watts	247 [248]	258 [260]	267 [269]	277 [279]	287 [289]	-	-	-	-	-	-
	CFM	1192 [1180]	1160 [1148]	1126 [1115]	1091 [1080]	1052 [1041]	-	-	-	-	-	-
MED- LOW ^(a)	Watts	-	352 [354]	361 [363]	372 [374]	382 [384]	392 [394]	404 [406]	416 [418]	-	-	-
	CFM	-	1272 [1259]	1243 [1231]	1214 [1202]	1186 [1174]	1154 [1142]	1116 [1105]	1072 [1061]	-	-	-
MED- HIGH	Watts	-	410 [410]	419 [419]	427 [427]	437 [437]	447 [447]	423 [423]	-	-	-	-
	CFM	-	1326 [1320]	1300 [1294]	1271 [1263]	1241 [1234]	1201 [1196]	1107 [1102]	-	-	-	-
HIGH	Watts	-	-	-	-	-	516 [519]	527 [530]	539 [542]	552 [555]	566 [569]	575 [578]
	CFM	-	-	-	-	-	1326 [1299]	1296 [1270]	1263 [1238]	1225 [1201]	1183 [1159]	1150 [1127]

Note: Airflow must not exceed 1350 CFM due to condensate blowoff.

^(a) Factory Default Setting.

Table 9. Indoor fan performance – model A5PA3042

A5PA3042		EXTERNAL STATIC PRESSURE (IN.WG) Horizontal Airflow [Cooling Down Airflow]										
Motor Speed		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
LOW	Watts	224 [228]	233 [238]	242 [247]	252 [257]	262 [267]	-	-	-	-	-	-
	CFM	1358 [1345]	1393 [1379]	1348 [1334]	1296 [1283]	1253 [1241]	-	-	-	-	-	-
MED- LOW ^(a)	Watts	306 [312]	316 [322]	327 [333]	337 [344]	348 [354]	359 [366]	369 [377]	382 [389]	395 [403]	-	-
	CFM	1521 [1506]	1490 [1475]	1448 [1433]	1391 [1377]	1362 [1348]	1338 [1325]	1315 [1302]	1307 [1293]	1254 [1241]	-	-
MED- HIGH	Watts	-	-	-	-	455 [464]	467 [477]	477 [487]	490 [499]	503 [513]	513 [523]	-
	CFM	-	-	-	-	1529 [1514]	1491 [1476]	1467 [1453]	1425 [1411]	1385 [1371]	1345 [1331]	-
HIGH	Watts	-	-	-	-	490 [499]	502 [511]	514 [523]	527 [536]	540 [550]	554 [564]	568 [578]
	CFM	-	-	-	-	1533 [1518]	1505 [1490]	1476 [1461]	1447 [1433]	1415 [1401]	1383 [1369]	1347 [1334]

Note: Airflow must not exceed 1575 CFM due to condensate blowoff.

^(a) Factory Default Setting.

Indoor Fan Performance (230V)

Table 10. Indoor fan performance – model A5PA3048

A5PA3048		EXTERNAL STATIC PRESSURE (IN.WG) Horizontal Airflow [Cooling Down Airflow]										
Motor Speed		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
LOW	Watts	302 [308]	313 [320]	324 [330]	332 [339]	346 [352]	-	-	-	-	-	-
	CFM	1583 [1567]	1542 [1526]	1502 [1487]	1460 [1445]	1415 [1401]	-	-	-	-	-	-
MED- LOW ^(a)	Watts	414 [422]	426 [434]	436 [444]	448 [457]	459 [468]	471 [480]	483 [493]	495 [505]	510 [520]	-	-
	CFM	1763 [1745]	1723 [1706]	1689 [1672]	1648 [1632]	1609 [1593]	1568 [1552]	1527 [1512]	1488 [1473]	1447 [1433]	-	-
MED- HIGH	Watts	-	577 [589]	591 [603]	604 [616]	617 [629]	631 [644]	643 [656]	655 [668]	599 [611]	-	-
	CFM	-	1786 [1768]	1757 [1739]	1729 [1712]	1700 [1683]	1675 [1658]	1648 [1632]	1624 [1608]	1504 [1489]	-	-
HIGH	Watts	-	-	-	-	-	613 [625]	631 [644]	643 [656]	647 [660]	611 [623]	-
	CFM	-	-	-	-	-	1769 [1751]	1728 [1711]	1688 [1671]	1652 [1635]	1545 [1530]	-

Note: Airflow must not exceed 1800 CFM due to condensate blowoff.

^(a) Factory Default Setting.

Table 11. Indoor fan performance – model A5PA3060


A5PA3060		EXTERNAL STATIC PRESSURE (IN.WG) Horizontal Airflow [Cooling Down Airflow]										
Motor Speed		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
LOW	Watts	515 [524]	523 [533]	533 [545]	544 [558]	-	-	-	-	-	-	-
	CFM	1857 [1831]	1831 [1802]	1800 [1765]	1766 [1728]	-	-	-	-	-	-	-
MED- LOW ^(a)	Watts	594 [611]	609 [627]	624 [642]	639 [658]	653 [672]	667 [686]	681 [701]	695 [715]	709 [730]	-	-
	CFM	2031 [2003]	2003 [1975]	1974 [1946]	1940 [1913]	1907 [1880]	1874 [1848]	1837 [1811]	1805 [1780]	1771 [1746]	-	-
MED- HIGH	Watts	749 [770]	759 [781]	769 [790]	779 [804]	788 [819]	803 [832]	816 [845]	830 [858]	845 [872]	860 [887]	-
	CFM	2083 [2054]	2058 [2030]	2032 [2010]	2003 [1976]	1974 [1946]	1943 [1911]	1911 [1879]	1877 [1848]	1843 [1817]	1807 [1781]	-
HIGH	Watts	900 [940]	910 [936]	921 [937]	932 [948]	941 [962]	956 [975]	969 [990]	983 [992]	997 [987]	1010 [985]	-
	CFM	2201 [2201]	2177 [2151]	2152 [2120]	2127 [2095]	2105 [2066]	2071 [2033]	2041 [1999]	2009 [1937]	1975 [1921]	1940 [1871]	-

Note: Airflow must not exceed 2250 CFM due to condensate blowoff.

^(a) Factory Default Setting.


Wiring Diagrams

Figure 1. A5PA3024 - 42



Wiring Diagrams

Figure 2. A5PA3024 - 42



PRINTED FROM D758129P01 REV C

Wiring Diagrams

Figure 4. A5PA3048





Figure 5. A5PA3060




NOTES:

1. CONNECTIONS SHOWN ARE FOR A TYPICAL THERMOSTAT. SEE SCHEMATIC SUPPLIED WITH THERMOSTAT FOR PROPER CONNECTIONS. LOW VOLTAGE WIRING TO UNIT MAY BE NEC CLASS 2.
2. MAXIMUM ADDITIONAL EXTERNAL LOAD (PILOT DUTY) BETWEEN "B" AND "R" OF 0.5 AMPS, 24 VAC IS AVAILABLE WHEN A HEATER IS INSTALLED.
3. SEE WIRING DIAGRAM WITH HEATER FOR DETAILS OF HEATER WIRING.
4. FOR 208 VOLT OPERATION MAKE THE FOLLOWING WIRING CHANGES: AT TNS, REMOVE I(A)RD WIRE AND CONNECT TO 208V TERMINAL ON THE TRANSFORMER.
5. IF ANY OF THE ORIGINAL WIRE AS SUPPLIED IN THIS UNIT MUST BE REPLACED, REPLACE IT WITH APPLIANCE WIRING MATERIAL RATED AT 105°C.
6. DO NOT REMOVE JUMPER UNLESS CONFIGURING AN EXTERNAL SWITCH.

24 VOLT TRANSFORMER FUSE REPLACEMENT FU 36 VOLT TYPE ATC-5 AMP

REFRIGERANT LEAK DETECTION AND MITIGATION CONTROL BOARD GREEN LED DIAGNOSTIC INDICATOR	
IDLE OR OFF	OFF
STARTUP	ON
24V Mode	FLASHING SLOW
NO ACTIVE ALARM	FLASHING SLOW
ACTIVE ALARM(REFRIGERANT LEAK, SENSOR COMMUNICATION OR SENSOR ERROR)	3 FLASHES
PAST REFRIGERANT DETECTED ALARM	4 FLASHES
PAST SENSOR COMMUNICATION ERROR	5 FLASHES
PAST SENSOR ERROR	6 FLASHES

LEGEND		
DEVICE DESIG	DESCRIPTION	LINE NUMBER
A2L_SR	A2L SENSOR	28
AH_BH	CONTACTOR, ELECTRIC HEATER	27
CC	CONTACTOR	12, 30
CF1	OUTDOOR FAN CAPACITOR	15
CPR	COMPRESSOR	11
CR	COMPRESSOR RUN CAPACITOR	11
FU	FUSE	26
H	HEATER RELAY	27, 33
HI_TEMP_SW	HIGH TEMPERATURE SWITCH	30
HPCO	HIGH-PRESSURE CUTOFF	30
IDM	INDOOR MOTOR	19, 36
LPCO	LOW-PRESSURE CUTOFF	30
ODM	OUTDOOR MOTOR	16
PPM	HEATER PLUG	27, 28
TNS	TRANSFORMER, 208/230V - 24V	22
IOL	INTERNAL OVERLOAD	
CN	CONNECTOR AND WIRE NUT	




IDM CONNECTION

WIRE COLOR DESIGNATION					
ABBR	COLOR	ABBR	COLOR	ABBR	COLOR
BK	BLACK	PR	PURPLE	GR	GREEN
BL	BLUE	RD	RED	YL	YELLOW
BR	BROWN	WH	WHITE	OR	ORANGE

Wiring Diagrams


Figure 6. A5PA3060



Full Perimeter Roof Mounting Curb

Figure 7. 2.0 to 3.0 ton models

BAYCURB050B Full Perimeter Roof Mounting Curb



The drawings on this page are prepared by the manufacturer in order to provide detail regarding job layout only. These drawings are not intended to be used as a basis to construct, build or modify the items depicted in the drawings. The manufacturer is not responsible for the unauthorized use of these drawings and expressly disclaims any liability for damages resulting from such unauthorized use.

All dimensions are in inches


	SERVICE CLEARANCE DIMENSIONS			
	A	B	C	D
TC/*WC*/ ASPA*/A5PH*	42.00	36.00	12.00**	24.00
DC/*YC*/A5PG*	42.00	36.00	12.00**	36.00

**42.00 WITH ECONOMIZER WITH 25% FRESH AIR ACCESSORY


Full Perimeter Roof Mounting Curb

Figure 8. 3.5 to 5.0 ton models

BAYCURB051B Full Perimeter Roof Mounting Curb



The drawings on this page are prepared by the manufacturer in order to provide detail regarding job layout only. These drawings are not intended to be used as a basis to construct, build or modify the items depicted in the drawings. The manufacturer is not responsible for the unauthorized use of these drawings and expressly disclaims any liability for damages resulting from such unauthorized use.



All dimensions are in inches

	SERVICE CLEARANCE DIMENSIONS			
	A	B	C	D
TC/*WC*/ A5PA*/A5PH*	42.00	36.00	12.00**	24.00
DC/*YC*/A5PG*	42.00	36.00	12.00**	36.00

** 42.00 WITH ECONOMIZER WITH 25% FRESH AIR ACCESSORY

Optional Equipment — Outside Air Damper

Table 12. BAYOSAH001 and 002A outside air damper
(Replaces filter/coil access panel)

	Manual Fresh Air Model	Unit Application Models	A	B	C	D
	BAYOSAH001A	2.0 — 3.0 Ton	22-7/16"	20-11/16"	12-3/8"	9-3/16"
	BAYOSAH002A	3.5 — 5.0 Ton	25-3/16"	20-11/16"	12-3/8"	9-3/16"


Table 13. BAYDMPR101 and 102A, 25% motorized outside air damper
(Mounts over horizontal return air opening)

	Manual Fresh Air Model	Unit Application Models	A	B	C	D	E
	BAYDM-PR101A	2.0 — 3.0 Ton	15-13/16"	11-13/16"	10-1/4"	11-1/2"	12-1/4"
	BAYDM-PR102A	3.5 — 5.0 Ton	18-3/16"	15-1/8"	10-1/4"	11-1/2"	12-1/4"


Note: The drawings on this page are prepared by the manufacturer in order to provide detail regarding job layout only. These drawings are not intended to be used as a basis to construct, build or modify the items depicted in the drawings. The manufacturer is not responsible for the unauthorized use of these drawings and expressly disclaims any liability for damages resulting from such unauthorized use.

Optional Equipment — Filter Rack

**Figure 9. BAYFLTR101 filter rack (2.0 to 3.0 ton models)
BAYFLTR201 (3.5 to 5.0 ton models)
(Mounts in filter/coil section)**




**Figure 10. BAYACCDOR1A hinged filter access door (2.0 to 3.0 ton models)
BAYACCDOR2A (3.5 to 5.0 ton models)
(Replaces filter/coil access panel)**



Note: The drawings on this page are prepared by the manufacturer in order to provide detail regarding job layout only. These drawings are not intended to be used as a basis to construct, build or modify the items depicted in the drawings. The manufacturer is not responsible for the unauthorized use of these drawings and expressly disclaims any liability for damages resulting from such unauthorized use.

Dimensional Data


Figure 11. Space on sides requirements



	2 - 3 TON Units		3.5 - 5 TON Units	
	RECOMMENDED SERVICE CLEARANCE mm [Inches]			
	W/ ECONOMIZER		W/ ECONOMIZER	
BACK SIDE	305 [12]	762 [30]	305 [12]	762 [30]
LEFT SIDE	762 [30]	914 [36]	914 [36]	1067 [42]
RIGHT SIDE	610 [24]	-	610 [24]	-
FRONT SIDE	1067 [42]	-	762 [30]	-
	CLEARANCE TO COMBUSTIBLE MATERIAL mm [Inches]			
BOTTOM	0		0	
BACK SIDE	25 [1]		25 [1]	
LEFT SIDE	152 [6]		152 [6]	
RIGHT SIDE	152 [6]		152 [6]	
FRONT SIDE	305 [12]		305 [12]	
TOP	914 [36]		914 [36]	
	DIMENSIONS mm [Inches]			
A	HEIGHT OF UNIT - TABLE NEXT PAGE			
BB	CENTER OF GRAVITY - TABLE NEXT PAGE			
CC	CENTER OF GRAVITY - TABLE NEXT PAGE			
DD -Depth	1049.02 [41-5/16]		1125.22 [44-5/16]	
EE -Width	1240.28 [48-27/32]		1487.17 [58-9/16]	
FF	469.33 [18-1/2]		551.48 [21-23/32]	

Note: The view labeled "Bottom side" represents the base as viewed looking up from underneath the unit.

Figure 12. Bottom and back duct openings



	Height mm [in]	PHYSICAL DIMENSIONS mm [in]												
	A -Height	B	C	D	E	F	G	H	I	J	K	L	M	N
A5PA3024	898.53 [35 - 3/8]	304.80 [12.0]	75.41 [2.93]	75.41 [2.93]	406.40 [16.0]	167.89 [6.61]	173.46 [6.8]	304.80 [12.0]	79.50 [3.13]	398.22 [15.68]	176.07 [6.93]	177.55 [6.99]	296.62 [11.68]	1155.45 [45.49]
A5PA3030	949.33 [37 - 3/8]													
A5PA3036														
A5PA3042	898.53 [35 - 3/8]	457.20 [18.0]	75.41 [2.97]	75.41 [2.97]	381.00 [15.0]	244.09 [9.61]	318.75 [12.55]	381.00 [15.0]	79.50 [3.13]	449.02 [17.68]	176.07 [6.93]	322.84 [12.71]	372.82 [14.68]	1402.34 [55.21]
A5PA3048	1000.13 [39 - 3/8]													
A5PA3060														

	Corner Weights KG [LBS]				SHIPPING WEIGHT KG [LBS]	UNIT WEIGHT KG [LBS]	Center Of Gravity mm [inch]	
	W1	W2	W3	W4			BB	CC
A5PA3024	60.3 [133]	36.8 [81]	26.1 [58]	41.0 [90]	197.8 [436]	164.2 [362]	479.8 [18.9]	527.8 [20.8]
A5PA3030	63.1 [139]	38.7 [85]	27.5 [61]	43.1 [95]	205.9 [454]	172.4 [380]	406.5 [16.0]	594.1 [23.4]
A5PA3036	63.9 [141]	38.9 [86]	27.7 [61]	43.7 [96]	207.7 [458]	174.2 [384]	414.3 [16.3]	697.6 [27.5]
A5PA3042	72.7 [160]	47.2 [104]	35.2 [78]	53.6 [118]	255.8 [564]	208.7 [460]	470.8 [18.5]	731.0 [28.8]
A5PA3048	75.0 [165]	45.0 [99]	33.8 [75]	54.4 [120]	255.4 [563]	208.2 [459]	433.0 [17.0]	743.3 [29.3]
A5PA3060	79.3 [175]	46.3 [102]	34.9 [77]	59.0 [130]	266.7 [588]	219.5 [484]	414.0 [16.3]	635.0 [25.0]

Mechanical Specifications

General

The units shall be horizontal airflow as shipped and convertible to downflow. All units shall be factory assembled, piped, internally wired and fully charged with refrigerant. Units shall be certified to UL 60335. All units shall be factory run tested to check cooling operation, fan and blower rotation and control or TXV sequence. Units shall be designed to operate at ambient temperatures between 115°F and 55°F in cooling as manufactured. Cooling performance shall be rated in accordance with AHRI standards.

Unit Casing

All components shall be mounted in a weather-resistant steel cabinet with an enamel finish. Access panels shall be provided for unit controls and indoor coil and fans. Indoor air section compartment shall be completely insulated with fireproof, permanent, odorless fiber material. Knockouts shall be provided for utility and control connections. Drain connections shall be provided to accommodate indoor water runoff.

Compressor

The compressor shall be hermetically sealed, high efficiency scroll compressors. Internal overcurrent and over temperature protection, internal pressure relief shall be standard. Other features include centrifugal oil pump, low vibration and noise.

Refrigeration System

All units shall have refrigerant control. Service pressure tap ports and a refrigerant line filter shall be standard.

Evaporator Coil (2–4 Ton Models) All aluminum micro channel, extruded tubes, mechanically bonded to aluminum fins, and factory pressure tested at 480 PSIG and leak tested at 250 to 300 PSIG. All units have TXV to control refrigerant flow.

Evaporator Coil (5 Ton Model) Internally enhanced 3/8-in. OD seamless copper tubing mechanically bonded to aluminum fins, factory pressure tested at 480 PSIG and leak tested at 250 to 300 PSIG. All units have TXV to control refrigerant flow.

Condenser Coil

The Spine Fin™ condenser coil shall be continuously wrapped, corrosion resistant all aluminum with minimum brazed joints. This coil is 3/8-in. OD seamless aluminum tubing glued to a continuous aluminum fin. Coils are lab tested to withstand 2,000 pounds of pressure per square inch. The outdoor coil provides low airflow resistance and efficient heat transfer. The coil is protected on all four sides by louvered panels.

Indoor Air Fan

Constant Torque, forward-curved, centrifugal wheel in a Composite Vortica® Blower housing. Motor shall have thermal overload protection and permanently lubricated motor bearings. Motor/blower assembly isolated from unit with rubber mounts.

Outdoor Fan

One direct-drive, statically and dynamically balanced propeller fan shall be used in a draw-through vertical discharge configuration. Permanently lubricated weather proof motor shall have built-in thermal overload protection.

System Controls

System controls include condenser fan, evaporator fan and compressor contactors.

Accessories Roof Curb

The roof curb shall be designed to mate with the unit and provide support and complete weathertight installation when properly installed. Adhesive back polyurethane sealing strips shall be provided to ensure an airtight seal between supply and return openings of the curb and unit. The roof curb design allows field fabricated ductwork to be connected directly to the curb. Curb ships knocked down for field assembly, and includes factory installed wood nailer strips.

Electric Heaters

Each heater assembly shall include power supply fusing if over 48 amps, automatic resetting limit switches and heat limiters for thermal protection. Heaters shall be provided with polarized plugs for quick connection to unit low voltage wiring. Electric heat modules shall be UL listed.

Single Source Power Entry

This accessory when used with electric heat accessory shall allow single source power connection to unit and heater combination. Single source power entry kits shall have specific matching heater(s). Kit shall include high voltage terminal blocks, fuse blocks and fuses, cut-to-length interconnecting wiring, and junction box (if required) to provide power sources with fuse protection as required for both the unit and accessory heater. Kit components shall install within the heater cabinet in the heater access section. Single source branch power circuit shall be protected and wired in accordance with local codes.

Fully Modulating Economizer

This accessory shall be field installed and be composed of the following items: 0–100 % fresh air damper, damper drive motor, fixed dry bulb enthalpy control, and low voltage pigtails for electrical connections. Solid state enthalpy or differential enthalpy control is optional. Economizer operations shall be controlled by the preset position of the enthalpy control. A barometric relief damper shall be standard with the economizer and provide a pressure operated damper that shall be gravity closing and prohibit entrance of outside air on equipment "off" cycle. Economizer requires BAYRLAY004B relay kit to interface the economizer to the heat pump.

Manual Outside Air Dampers

Rain hood and screen shall be field installed. Suitable for up to 25% outside air.

Start Kit

Extra compressor starting capacity for single phase equipment.

Control Options

Standard Indoor Thermostats

Two stage heating/cooling or one stage heating/cooling thermostats shall be available in either manual or automatic changeover.

Programmable Electronic Night Setting Thermostat

Programmable electronic thermostat shall provide heating setback and cooling setup with 7–day programming capability. 1H/1C or 2H/2C models available.

About Trane and American Standard Heating and Air Conditioning

Trane and American Standard create comfortable, energy efficient indoor environments for residential applications. For more information, please visit www.trane.com or www.americanstandardair.com.



The AHRI Certified mark indicates company participation in the AHRI Certification program. For verification of individual certified products, go to ahridirectory.org.

The manufacturer has a policy of continuous data improvement and it reserves the right to change design and specifications without notice. We are committed to using environmentally conscious print practices.